



Lease Life
to Man-Made
Structures

SUPERSHIELD

PUMP CLEANER

Cleaning agent for specific interventions with water-reactive resins



PRODUCT DESCRIPTION

SUPERSHIELD PUMP CLEANER is a specialized cleaning agent designed for use with injection equipment involved in stopping water infiltration in buildings. This oily rinsing detergent features low toxicity and a high solvent capacity, making it effective for cleaning non-hardened polyurethanes. It is specifically formulated to clean and lubricate the internal hydraulic circuits of both manual and electric pumping systems, ensuring efficient operation and maintenance of injection equipment.

AREAS OF APPLICATION

SUPERSHIELD PUMP CLEANER is specifically designed for cleaning equipment used for water-reactive polyurethane injections in masonry. It effectively removes non-hardened polyurethane residues, ensuring that injection equipment is maintained in optimal condition for future use.



APPLICATION GUIDELINES

After finishing injection operations with water reactive polyurethane based masonry products, thoroughly clean the pumping equipment before storage. Start by circulating SUPERSHIELD PUMP CLEANER, undiluted, through the hydraulic circuits for a few minutes to clean and lubricate the internal components. Ensure to leave a small amount of the cleaner inside the circuits to maintain lubrication during periods when the pump is not in use. Always shake the product well before each use and apply it within a temperature range of 10°C to 40°C.

HEALTH AND SAFETY

To ensure safety, avoid direct contact with skin and eyes. Always wear safety glasses, gloves, and protective clothing. In the event of contact with eyes, rinse immediately with water and seek medical advice. If resin contacts skin, rinse thoroughly with water. Manage spills by absorbing them with sand and disposing according to local regulations. For further instructions on a safe use of the product please refer to safety datasheets.

STORAGE

The unopened package has a shelf life of 12 months from the date of manufacture when stored in a dry, cool place. To maintain its quality, it is important to protect the package from frost.

PACKAGING

10 Kg Cans.

WARRANTY

Supershield warrants that its products will be free from material defects and will comply with the specifications provided in their respective technical data sheets. If any product is proven to be defective, Supershield's liability will be limited to the replacement of the product. Supershield will not be liable for any incidental or consequential damages. No other warranties, express or implied, shall apply, including warranties of merchantability or fitness for a particular purpose. It is the user's responsibility to determine the suitability of the product for their intended use and to assume all risks and liabilities associated with its application. Supershield reserves the right to alter the properties of its products without prior notice.